



- 可量測扭力及螺絲栓緊之後的角度。
- 配件：收納用鐵製工具箱x1，出廠校驗報告(符合ISO品質認證規範)x1，說明書(中/英)x1，AA電池x2
- Can measurement the degree after tighten the screw or nut.
- Content : Provide storage steel box x1, Certificate of calibration report (Using ISO specification) x1, Operator's menu(Bilingual) x1, AA battery x2

SPECIFICATIONS:

產品編號 Item No.	精度 Accuracy	棘輪方頭 Driver	設定範圍 Setting Range	建議使用範圍 Suggested Range	最小量測單位 Min. Scale Unit	扳手長度 Wrench Length (mm)	扳手重量 Wrench Weight (±50g)
WA-30-1	出廠精度 CW:±1% 預設精度 CW:±1.5% CCW:±2.5%	1/4"	1.5~30 Nm / 1°~360°	4.5~30 Nm	0.1 Nm / 1°	406	770
WA-135-2		3/8"	6.8~135 Nm / 1°~360°	20~135 Nm		434	886
WA-135-3		1/2"	6.8~135 Nm / 1°~360°	20~135 Nm		454	1080
WA-200-3			10~200 Nm / 1°~360°	30~200 Nm		565	1300
WA-340-3		17~340 Nm / 1°~360°	50~340 Nm	666		1420	
WA-600-4		60~600 Nm / 1°~360°	90~600 Nm	940		3800	
WA-800-4		80~800 Nm / 1°~360°	120~800 Nm	1235		4800	
WA-1000-4		100~1000 Nm / 1°~360°	150~1000 Nm	1235		4800	

※ 1 Nm = 10.2 kgf-cm = 0.738 lbf-ft = 8.851 lbf-in